

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Cold Finished Carbon, Stainless and Alloy Steels CAS Number: Not applicable Synonyms: Steels Use/Description: Cold Finish Steel Products, Rivets, Bolts, Lugs

Nucor Location	s 24 Hour Contact – CHEMTR	EC 1-800-424-9300
Nucor Cold Finish South Carolina 2800 N. Governor Williams Hwy. Darlington, South Carolina 29540 1-843-395-8689	Nucor Cold Finish Utah 1875 West Hwy 13, South Brigham City, Utah, 84302 1-435-734-9433	Laurel Steel 5400 Harvester Rd Burlington, ON, Canada L7R 3Y8 1-800-265-6811
Nucor Cold Finish Nebraska PO Box 94 2301 West Omaha Avenue Norfolk, Nebraska 68701 1-402-644-8600	Nucor Cold Finish Wisconsin, Inc. 7200 South 6 th Street Oak Creek, Wisconsin 53154 1-414-764-0220	St. Louis Cold Drawn 1060 Pershall Rd St. Louis, MO 63137 1-314-867-4301
Nucor LMP, Inc. 2000 East First Street Maryville, MO 64468 1-660-582-3127	Nucor Bright Bar Ohio 555 Collins Blvd Orrville, OH 44667 1-330-682-5555	Aceros Trefilados De Precision Carretera Apodaca Santa Rosa #502 Monterrey, Mexico 011-52-818-385-2727

For general product information, contact facility as listed above. For emergencies, use the 24 Hour Contact.

EMERGENCY OVERVIEW

2. HAZARDS IDENTIFICATION

STEEL PRODUCTS AS SOLD BY NUCOR ARE NOT HAZARDOUS PER OSHA GHS 29 CFR 1910, 1915, 1926. However, individual customer processes, (such as welding, sawing, brazing, grinding, abrasive blasting, and machining) may result in the formation of fumes, dust (combustible or otherwise), and/or particulate that may present the following hazards:

OSHA Hazards:	Carcinogen			
	Skin Sensitizer			
	Target Organ Effect – Lungs			
	Reproductive Toxicant*			

<u>GHS Classification</u>: Carcinogenicity (Category 2) Skin Sensitization (Category 1) Specific Target Organ Toxicity-Repeated Exposure (Category 1) Reproductive Toxicity (Category 1A)*

Pictogram(s):



Hazard Statement(s)

H317: Dust/fumes may cause an allergic skin reaction.

H351: Dust/fumes suspected of causing cancer via inhalation.

H372: Inhalation of dust/fumes causes damage to respiratory tract through prolonged or repeated exposure

H372: Dust/fumes cause damage to the central nervous system and systems for reproduction through prolonged or repeated exposure.*

H360: Dust/fumes may damage fertility or the unborn child.*

Precautionary Statement(s)

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing dust/fumes.

P281: Use personal protective equipment as required.

P308+P313: If exposed or concerned: Get medical advice/attention.

* - applies only to dust/fumes generated from leaded steel products

Potential Health Effects

Eye Contact

Dusts or particulates may cause mechanical irritation including pain, tearing, and redness. Scratching of the cornea can occur if eye is rubbed. Fumes may be irritating. Contact with the heated material may cause thermal burns.

Skin Contact

Dusts or particulates may cause mechanical irritation due to abrasion. Coated steel may cause skin irritation in sensitive individuals (see Section 16 for additional information.) Some components in this product are capable of causing an allergic reaction, possibly resulting in burning, itching and skin eruptions. Contact with heated material may cause thermal burns.

Inhalation

Dusts may cause irritation of the nose, throat, and lungs. Excessive inhalation of metallic fumes and dusts may result in metal fume fever, an influenza-like illness. It is characterized by a sweet or metallic taste in the mouth, accompanied by dryness and irritation of the throat, cough, shortness of breath, pulmonary edema, general malaise, weakness, fatigue, muscle and joint pains, blurred vision, fever and chills. Typical symptoms last from 12 to 48 hours.

Ingestion

Not expected to be acutely toxic via ingestion based on the physical and chemical properties of the product. Swallowing of excessive amounts of the dust may cause irritation, nausea, and diarrhea.

Potential Fire and Explosion Hazards

Under normal conditions, steel products do not present fire or explosion hazards, and dust generated by handling steel products is oxidized and not combustible. Processing of steel product by some individual customers may produce potentially combustible dust that may represent a fire or explosion hazard.

Chronic or Special Toxic Effects

Repeated exposure to fine dusts may inflame the nasal mucosa and cause changes to the lung. In addition, a red-brown pigmentation of the eye and/or skin may occur. Welding fumes have been associated with adverse health effects. Contains components that may cause cancer or reproductive effects. The following components are listed by NTP, OSHA, or IARC as carcinogens: Nickel, chromium (hexavalent), cobalt, lead, cadmium, antimony (trioxide), arsenic, beryllium. See Section 11, for additional, specific information on effects noted above.

Target Organs

Overexposure to specific components of this product that are generated in dusts or fumes may cause adverse effects to the following organs or systems: eyes, skin, liver, kidney, central nervous system, cardiovascular system, respiratory system.

Medical Conditions Aggravated by Exposure

Diseases of the skin such as eczema may be aggravated by exposure. Also, disorders of the respiratory system including asthma, bronchitis, and emphysema. Long-term inhalation exposure to agents that cause pneumoconiosis (e.g. dust) may act synergistically with inhalation of oxide fumes or dusts of this product.

		CAS No.	% Weight	Exposure Limits			
					ACGIH TLV (mg/m ³)		OSHA PEL (mg/m ³)
Base Metal:							
Iron	(Fe)	7439-89-6	Balance	5	Oxide Dust/Fume	10	Oxide Dust/Fume
<u>Alloying</u> Elements							
Aluminum	(AI)	7429-90-5	<0.25	10	Dust	15	Dust
Arsenic	(As)	7440-38-2	<0.5	0.01	As Arsenic (A1 Carcinogen)	0.01	As Arsenic
Beryllium	(Be)	7440-41-7	<1.0	0.00	As Beryllium (A1 Carcinogen) As Beryllium (STEL)	0.002 0.005	As Beryllium As Beryllium (Ceiling)
				0.01	As Derymann (OTEE)	0.000	As Derymum (Cennig)
Bismuth	(Bi)	7440-69-9	<1.5		Not established		Not established
Boron	(B)	7440-42-8	<.01-1.0	10	Oxide Dust	15	Oxide Dust
Carbon Chromium	(C)	7440-44-0	<1.2		Not Established		Not Established
(Stainless grades)	(Cr)	7440-47-3	4-20	0.5	Metal	1	Metal
Chromium (Carbon grades)	(Cr)	7440-47-3	0.01-2.5 Some grades up to 11%	0.5	Metal	1	Metal
Cobalt	(Co)	7440-48-4	<0.5	0.02	As Cobalt (A3 Carcinogen)	0.1	Metal/Dust/Fume
Copper	(Cu)	7440-50-8	1.9	1 0.2	Dust Fume	1 0.1	Dust Fume
Lead (Leaded Grades)	(Pb)	7439-92-1	0.15-0.35	0.05	Dust / Fume (A3 Carcinogen)	0.05	Dust / Fume
Magnesium	(Mg)	7439-95-4	<0.9 Some Grades up to 10.02%		Not Established		Not Established
Manganese	(Mn)	7439-96-5	0-2.5	0.2	Elemental Mn and Inorg Compounds	5	Fume (Ceiling)
Molybdenum	(Mo)	7439-98-7	0-1.2	10	Insoluble Compounds	15	Insoluble Compounds
Nickel	(Ni)	7440-02-0	<4.0 Some grades up to 10%	1.5	Metal	1	Metal and Insoluble Compounds
Silicon	(Si)	7440-21-3	<3.0	10	Dust	15	Dust
Vanadium	(V)	7440-62-2	<0.25	0.05	Oxide Dust/Fume	0.5 0.1	Oxide Dust (Ceiling) Oxide Fume (Ceiling)
Zinc	(Zn)	7440-66-6	<10.0 Some grades up to 10%	10 5 10	Oxide Dust OxideFume Oxide Fume (STEL)	5 10	Oxide Fume Oxide Dust

3. COMPOSITION/INFORMATION ON INGREDIENTS

NOTE: No permissible exposure limits (PEL) or threshold limit values (TLV) exist for steel. The above listing is a summary of elements used in alloying Nucor Cold Finish Products. Various grades of steel will contain different combinations of these elements and/or trace materials. Exact specifications may be found by calling the division and asking for a specifications sheet.

4. FIRST AID MEASURES

Eye Contact- In case of overexposure to dusts or fumes, immediately flush eyes with plenty of water for at least 15 minutes occasionally lifting the eye lids. Get medical attention if irritation persists. Thermal burns should be treated as medical emergencies.

Skin Contact - In case of overexposure to dusts or particulates, wash with soap and plenty of water. Get medical attention if irritation develops or persists. If thermal burn occurs, flush area with cold water and get immediate medical attention.

Inhalation - In case of overexposure to dusts or fumes, remove to fresh air. Get immediate medical attention if symptoms described in this Safety Data Sheet (SDS) develop.

Ingestion - Not considered an ingestion hazard. However, if excessive amounts of dust or particulates are swallowed, treat symptomatically and supportively. Get medical attention.

Notes to Physician - Inhalation of metal fume or metal oxides may produce an acute febrile state, with cough, chills, weakness, and general malaise, nausea, vomiting, muscle cramps, and remarkable leukocytosis. Treatment is symptomatic, and condition is self limited in 24-48 hours. Chronic exposure to dusts may result in pneumoconiosis of mixed type.

5. FIRE FIGHTING MEASURES

Flash Point (Method) - Not applicable

Flammable Limits (% volume in air) - Not applicable

Auto ignition Temperature - Not applicable

Extinguishing Media - For molten metal, use dry powder or sand. For steel dust use or dry sand, water, foam, argon or nitrogen.

Special Fire Fighting Procedures - Do not use water on molten metal. Do not use Carbon Dioxide (CO₂). Firefighters should not enter confined spaces without wearing NIOSH/MSHA approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.

Unusual Fire or Explosion Hazards - Steel products do not present fire or explosion hazards under normal conditions. Any non-oxidized fine metal particles/ dust generated by grinding, sawing, abrasive blasting, or individual customer processes may produce materials that the customer should test for combustibility and other hazards in accordance with applicable regulations. High concentrations of combustible metallic fines in the air may present an explosion hazard.

6. ACCIDENTAL RELEASE MEASURES

Precautions if Material is Spilled or Released - Emergency response is unlikely unless in the form of combustible dust. Avoid inhalation, eye, or skin contact of dusts by using appropriate precautions outlined in this SDS (see section 8). Fine turnings and small chips should be swept or vacuumed and placed into appropriate disposable containers. Keep fine dust or powder away from sources of ignition. Scrap should be reclaimed for recycling. Prevent materials from entering drains, sewers, or waterways. Specific standards and regulations may be applicable to materials generated by individual customer processes. As appropriate, these standards and regulations should be consulted for applicability.

Fire and Explosion Hazards - Some customer processes may generate combustible dust that may require specific precautions when cleaning spills or releases of dust.

Environmental Precautions - Some grades of steel may contain reportable quantities of alloying elements. See Section 15 for additional information.

Waste Disposal Methods - Dispose used or unused product in accordance with applicable Federal, State, and Local regulations. Please recycle.

7. HANDLING AND STORAGE

Storage Temperatures - Stable under normal temperatures and pressures.

Precautions to be Taken in Handling and Storing - Store away from strong oxidizers. Dusts and/or powders, alone, or combined with process specific fluids, may form explosive mixtures with air. Applicable Federal, state and local laws and regulations may require testing dust generated from processing of steel products to determine if it represents a fire or explosion hazard and to determine appropriate protection methods. Avoid breathing dusts or fumes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Operations with potential for generating high concentrations of airborne particulates or fumes should be evaluated and controlled as necessary.

Eye Protection - Use safety glasses. Dust resistant safety goggles are recommended under circumstances where particles could cause mechanical injury such as grinding or cutting. Face shield should be used when welding or cutting.

Skin - Appropriate protective gloves should be worn as necessary. Good personal hygiene practices should be followed including cleansing exposed skin several times daily with soap and water, and laundering or dry cleaning soiled work clothing.

Respiratory Protection - NIOSH/MSHA approved dust/fume/mist respirator should be used to avoid excessive exposure. See Section 3 for component material information exposure limits. If such concentrations are sufficiently high that this respirator is inadequate, or high enough to cause oxygen deficiency, use a positive pressure self-contained breathing apparatus (SCBA). Follow all applicable respirator use, fitting, and training standards and regulations.

Ventilation - Provide general and/or local exhaust ventilation to control airborne levels of dust or fumes below exposure limits.

Exposure Guidelines - No permissible exposure limits (PEL) or threshold limit values (TLV) exist for steel. See Section 3 for component materials. Various grades of steel will contain different combinations of these elements. Trace elements may also be present in minute amounts.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor – Silver grey to grey black with metallic luster. Boiling Point - Not applicable Melting Point - Approximately 2800 °F pH - Not applicable Specific Gravity (at 15.6 °C) - Not applicable Density (at 15.6 °C) - Not applicable Vapor Pressure - Not applicable Vapor Density (air = 1) - Not applicable % Volatile, by Volume - Not applicable Solubility in Water - Insoluble. Evaporation Rate (Butyl Acetate = 1) - Not applicable Other Physical and Chemical Data - None

10. STABILITY AND REACTIVITY

Stability - Stable

Conditions to Avoid - Steel at temperatures above the melting point may liberate fumes containing oxides of iron and alloying elements. Avoid generation of airborne fume.

Hazardous Polymerization - Will not occur.

Incompatibility (Materials to Avoid) - Reacts with strong acids to form hydrogen gas. Do not store near strong oxidizers.

Hazardous Decomposition Products - Metallic fumes may be produced during welding, burning, grinding, and possibly machining or any situation with the potential for thermal decomposition. Refer to ANSI Z49.1

11. TOXICOLOGICAL INFORMATION

The primary component of this product is iron. Long-term exposure to iron dusts or fumes can result in a condition called siderosis which is considered to be a benign pneumoconiosis. Symptoms may include chronic bronchitis, emphysema, and shortness of breath upon exertion. Penetration of iron particles in the skin or eye may cause an exogenous or ocular siderosis which may be characterized by a red-brown pigmentation of the affected area. Ingestion overexposures to iron may affect the gastrointestinal, nervous, and hematopoietic system and the liver. Iron and steel founding, but not iron or iron oxide, has been listed as carcinogenic (Group 1) by IARC.

When this product is welded, fumes are generated. Welding fumes may be different in composition from the original welding product, with the chief component being ordinary oxides of the metal being welded. Chronic health effects (including cancer) have been associated with the fumes and dusts of individual component metals (see above), and welding fumes as a general category have been listed by IARC as a carcinogen (Group 2B). There is also limited evidence that welding fumes may cause adverse reproductive and fetal effects. Evidence is stronger where welding materials contain known reproductive toxins, e.g., lead which may be present in the coating material of this product.

Breathing fumes or dusts of this product may result in metal fume fever, which is an illness produced by inhaling metal oxides. These oxides are produced by heating various metals including cadmium, zinc, magnesium, copper, antimony, nickel, cobalt, manganese, tin, lead, beryllium, silver, chromium, aluminum, selenium, iron, and arsenic. The most common agents involved are zinc and copper.

This product may contain small amounts of manganese. Prolonged exposure to manganese dusts or fumes is associated with "manganism", a Parkinson-like syndrome characterized by a variety of neurological symptoms including muscle spasms, gait disturbances, tremors, and psychoses.

This product may contain small amounts of cadmium. Primary target organs for cadmium overexposure are the lung and the kidney. Because of its cumulative nature, chronic cadmium poisoning can cause serious disease which takes many years to develop and may continue to progress despite cessation of exposure. Progression of the disease may not reflect current exposure conditions. It is also capable of causing a painful osteomalacia called "Itai-Itai" in postmenopausal women, and has caused developmental effects and/or reproductive effects in male and female animals. Cadmium is a listed carcinogen by NTP, OSHA, and IARC (Group 1).

This product may contain small amounts of chromium. Prolonged and repeated overexposure to chromium dusts or fumes may cause skin ulcers, nasal irritation and ulceration, kidney damage and cancer of the respiratory system. Chromium is skin sensitizer. Cancer is generally attributed to the hexavalent (+6) form of chromium which is listed as a carcinogen by NTP and IARC (Group 1).

This product may contain small amounts of nickel. Prolonged and repeated contact with nickel may cause sensitization dermatitis. Inhalation of nickel compounds has caused lung damage as well as sinus, nasal and lung cancer in laboratory animals. Nickel is a listed carcinogen by NTP and IARC (Group 1).

This product may contain small amounts of vanadium. Adverse effects from dermal, inhalation or parenteral exposure to various vanadium compounds have been reported. The major target for vanadium pentoxide toxicity is the respiratory tract. Fumes or dust can cause severe eye and respiratory irritation, and systemic effects. Chronic bronchitis, green tongue, conjunctivitis, pharyngitis, rhinitis, rales, chronic productive cough, and tightness of the chest have been reported following overexposure. Allergic reactions resulting from skin and inhalation exposures have also been reported. A statistical association between vanadium air levels and lung cancer has been suggested, but vanadium currently is not regarded as a human carcinogen.

This product may contain small amounts of lead. Lead can accumulate in the body. Consequently, exposure to fumes or dust may produce signs of polyneuritis, diminished vision and peripheral neuropathy, such as tingling and loss of feeling in fingers, arms and legs. Lead is a known reproductive and developmental toxin. It is also associated with central nervous system disorders, anemia, kidney dysfunction and neurobehavioral abnormalities. The brain is a major target organ for lead exposure. Elemental lead is listed as an IARC 2B carcinogen.

The product may contain small amounts of copper. Copper dust and fumes can irritate the eyes, nose and throat causing coughing, wheezing, nosebleeds, ulcers and metal fume fever. Other effects from repeated inhalation of copper fumes include a metallic or sweet taste, and discoloration of skin, teeth or hair. Copper also may cause an allergic skin reaction. Overexposure to copper can affect the liver.

12. ECOLOGICAL INFORMATION

Aquatic Ecotoxicological Data - No specific information available on this product. **Environmental Fate Data** - No specific information available on this product.

13. DISPOSAL CONSIDERATIONS

Recovery and reuse, rather than disposal, should be the ultimate goal of handling efforts. Dispose in accordance with federal, state, and local health and environmental regulations. Prevent materials from entering drains, sewers, or waterways.

14. TRANSPORT INFORMATION

DOT Proper Shipping Name - Not regulated DOT Hazard Classification - Not regulated UN/NA Number - Not applicable DOT Packing Group - Not applicable Labeling Requirements - Not applicable Placards - Not applicable DOT Hazardous Substance - Not applicable DOT Marine Pollutant - Not applicable

15. REGULATORY INFORMATION

This product is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, dusts and fumes from this product may be combustible or hazardous and require protection to comply with applicable Federal, state and local laws and regulations.

California Proposition 65:

- ▲ WARNING: This product can expose you to chemicals including antimony [oxide], arsenic, beryllium, chromium [hexavalent], cobalt, cadmium, lead, and nickel which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.
- Massachusetts Substance List: Aluminum, Antimony, Arsenic, Beryllium, Boron, Cadmium, Chromium, Cobalt, Copper, Lead, Magnesium, Manganese, Molybdenum, Nickel, Nitrogen, Phosphorus, Selenium, Silicon, Sulfur, Tellurium, Tin, Titanium, Tungsten, Vanadium, Zinc
- Pennsylvania Hazardous Substance List: Aluminum, Antimony, Arsenic, Beryllium, Boron, Cadmium, Chromium, Cobalt, Copper, Lead, Magnesium, Manganese, Molybdenum, Nickel, Nitrogen, Phosphorus, Selenium, Silicon, Sulfur, Tellurium, Tin, Titanium, Tungsten, Vanadium, Zinc
- New Jersey Hazardous Substance List: Aluminum, Antimony, Arsenic, Beryllium, Boron, Cadmium, Chromium, Cobalt, Copper, Lead, Magnesium, Manganese, Molybdenum, Nickel, Nitrogen, Phosphorus, Selenium, Silicon, Sulfur, Tellurium, Tin, Titanium, Tungsten, Vanadium, Zinc

Toxic Substances Control Act (TSCA)

Components of this product are listed on the TSCA Inventory.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA)

Steel is not reportable, however, it contains hazardous substances that may be reportable if released in pieces with diameters less than or equal to 0.004 inches.

Chemical Name	Reportable Quantity (in Ib)
Arsenic	1
Beryllium	10
Chromium	5,000
Copper	5,000
Lead (leaded steel only)	10
Nickel	100
Zinc	1,000

Superfund Amendments and Reauthorization Act of 1986 (SARA), Title III

SECTION 311/312 HAZARD CATEGORIES: Immediate Health Effect, Delayed Health Effect

This product contains the following EPCRA Section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right – To – Know Act of 1986 (40 CFR 372):

SECTION 313 REPORTABLE INGREDIENTS:

Chemical Name	CAS Number	Concentration (% by weight)	Reportable
Arsenic	7440-38-2	<0.5	Yes – Greater than 0.1%
Beryllium	7440-41-7	<1.0	Yes – Greater than 0.1%
Bismuth	7440-69-9	<1.5	Yes – Greater than 0.1%
Chromium	7440-47-3	0.01-2.5, Some up to 20%	Yes – Greater than 0.1%
Cobalt	7440-48-4	<0.5	Yes – Greater than 0.1%
Copper	7440-50-8	1.9	Yes – Greater than 1%
Lead	7439-92-1	0-0.08 (0.15-0.35 leaded grades)	Yes – No de minimis level
Manganese	7439-96-5	0-2.5	Yes – Greater than 1%
Nickel	7440-02-0	<4.0, Some up to 10%	Yes – Greater than 0.1%
Zinc	7440-66-6	<0.9, Some up to 10%	Yes – Greater than 1%

Concentrations based on analytical data and process knowledge of typical products distributed by the facility.

16. OTHER INFORMATION

This SDS covers Nucor product as delivered from the Nucor facility, but does not include chemicals that may be applied by subsequent handlers and/or distributors of this product. This could include a variety of materials including oils, paints, galvanization, etc. that are not included in this SDS. Additionally, specialty orders may require application of coating material not listed in this SDS. SDSs for any Nucor-applied specialty coating will be provided separately. During welding, precautions should be taken for airborne contaminants that may originate from components of the welding rod. Arc or spark generated when welding or burning could be a source of ignition for combustible and/or flammable materials. The information in this SDS was obtained from sources which we believe are reliable; however, the information is provided without any representation or warranty, expressed or implied, regarding the accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of this product.